

275F

MICRO FUSE


Type:275F 2.4DiaX7.2
Fast Acting
UL 248-14 GB9364.3
Lead Free



Electrical Characteristics:

Ampere rating %of Ampere rating Opening time

63mA-10A	100%	4hours min (UL,GB)
	200%	5second max.(UL,GB)
	275%	300ms(GB)
	400%	300ms(GB)
	1000%	4ms(GB)



Part Number	Current mA/A	Vollage V	Breaking Capacity	Voltage Drop {IEC 127-III} max.mV	Melting Integral Max,A ² S	Safety Approval		
						UL	CCC	
275F0063	63	125	300A dc 50A ac	2,230	0.0002	*	*	
275F0125	125			500	0.0010	*	*	
275F0250	250			1,000	0.0070	*	*	
275F0315	315			1,000	0.0065	*	*	
275F0375	375			1,000	0.0141	*		
275F0400	400			1,000	0.0110		*	
275F0500	500			1,000	0.0250	*	*	
275F0630	630			500	0.0397		*	
275F0750	750			275	0.0562	*		
275F0800	800			275	0.0420		*	
275F1100	1			275	0.1000	*	*	
275F1125	1.25			275	0.1380		*	
275F1150	1.5			275	0.3375	*		
275F1160	1.6			275	0.3840		*	
275F1200	2			250	0.4800	*	*	
275F1250	2.5			250	1.0000	*	*	
275F1300	3			250	1.8000	*		
275F1315	3.15			250	1.9845		*	
275F1350	3.5			250	2.4500	*		
275F1400	4			225	3.2000	*	*	
275F1500	5			225	5.0000	*	*	
275F1700	7			150	11.00000	*		
275F2100	10			50A dc	125	36.0000		

Note: Safety Approve and Specification subject to change without prior notice

Packaging: Bulk 5,000 pieces per box



富源电子科技有限公司

富源电子科技有限公司

HTTP: //www.fuyuanfuse.com

地址: 东莞市东城区下桥银桥工业区

E-mail: fuyuanfuse@163.com

TEL: 0769-23115816 FAX: 0769-23115819