


275T

MICRO FUSE

Type: 275T 2.4DiaX7.2
 Time-lag
 UL 248-14 GB9364.3
 Lead Free

Electrical Characteristics:
 Ampere rating %of Ampere rating Opening time



富源电子科技有限公司

Rated current	1 In	2 In		3 In		10 In	
	MIN	MIN	MAX	MIN	MAX	MIN	MAX
375mA~7A	4hours	1sec	60sec	0.2sec	1sec	0.02sec	0.1sec

Part Number	Current mA/A	Voltage V	Breaking Capacity	Voltage Drop {IEC 127-III} max.mV	Melting Integral Max,A ² S	Safety Approval
						UL
275T0375	375	125	50Aac	1.7400	0.0850	
275T0500	500			1.1300	0.2100	
275T0750	750			0.4600	0.0760	
275T1	1			0.2670	2.0100	
275T1.5	1.5			0.1160	3.9400	*
275T2	2			0.7120	7.6000	*
275T2.25	2.25			0.0630	9.2800	*
275T2.5	2.5			0.0520	13.000	*
275T3	3			0.0380	21.000	*
275T3.5	3.5			0.0240	26.800	*
275T4	4			0.0194	35.000	*
275T5	5			0.0133	54.800	*
275T7	7			0.0092	105.00	*

Note: Safety Approve and Specification subject to change without prior notice

Packaging: Bulk 5,000 pieces per box

富源电子科技有限公司

HTTP: //www.fuyuanfuse.com

地址: 东莞市东城区下桥银桥工业区

E-mail: fuyuanfuse@163.com

TEL: 0769-23115816 FAX: 0769-23115819